

C8L

Origin on the non-motor side is selectable

Ordering method

C8L	Model	Lead 20: 20mm 10: 10mm 5: 5mm	Brake No entry: With no brake BK: With brake	Option Origin position change None: Standard Z: Non-motor side	Stroke 150 to 1050 (50mm pitch)	Cable length ^{Note 1} 3L: 3.5m 5L: 5m 10L: 10m 3K/5K/10K (Flexible cable)	TSX	Positioner ^{Note 2} TS-X	Driver: Power-supply voltage / Power capacity 105: 100V/100W or less 205: 200V/100W or less	LCD monitor No entry: None L: With LCD	I/O selection NP: NPN PN: PNP CC: CC-Link DN: DeviceNet™ EP: EtherNet/IP™ PT: PROFINET GW: No I/O board ^{Note 3}	Battery B: With battery (Absolute) N: None (Incremental)
	SR1-X	Controller	05	Driver: Power capacity 05: 100W or less	Usable for CE No entry: Standard E: CE marking	I/O selection N: NPN P: PNP CC: CC-Link DN: DeviceNet™ PB: PROFIBUS	Battery B: With battery (Absolute) N: None (Incremental)					
	RDV-X	Driver	2	Power-supply voltage 2: AC200V	Driver: Power capacity 05: 100W or less	RBR1	Regenerative unit					


Note 1. The robot cable is standard cable (3L/5L/10L), but can be changed to flexible cable. See P.614 for details on robot cable.
 Note 2. See P.522 for DIN rail mounting bracket.
 Note 3. Select this selection when using the gateway function. For details, see P.66.

Basic specifications

AC servo motor output (W)	100
Repeatability ^{Note 1} (mm)	+/-0.01
Deceleration mechanism	Ball screw ϕ 15
Ball screw lead (mm)	20 10 5
Maximum speed ^{Note 2} (mm/sec)	1000 600 300
Maximum payload (kg)	Horizontal 20 40 50 Vertical 4 8 16
Rated thrust (N)	84 169 339
Stroke (mm)	150 to 1050 (50mm pitch)
Overall length (mm)	Horizontal Stroke+325 Vertical Stroke+360
Maximum outside dimension of body cross-section (mm)	W80 x H75
Cable length (m)	Standard: 3.5 / Option: 5, 10
Degree of cleanliness	CLASS 10 ^{Note 3}
Intake air (Nl/min)	30 to 90 ^{Note 4}

Note 1. Positioning repeatability in one direction.
 Note 2. When the stroke is longer than 700mm, resonance of the ball screw may occur depending on the operation conditions (critical speed). In this case, reduce the speed setting on the program by referring to the maximum speeds shown in the table below.
 Note 3. Per 1cf (0.1um base), when suction blower is used.
 Note 4. The necessary intake amount varies depending on the use conditions and environment.


Allowable overhang



	Horizontal installation (Unit: mm)			Wall installation (Unit: mm)			Vertical installation (Unit: mm)		
	A	B	C	A	B	C	A	C	
Lead 20	5kg 259	122	179	5kg 147	100	220	2kg 255	260	
	10kg 149	55	89	10kg 53	32	97	4kg 111	115	
	15kg 100	33	56	15kg 17	10	39	2kg 300	302	
	20kg 95	22	41	20kg 0	0	0	4kg 131	133	
Lead 10	10kg 251	61	130	10kg 87	41	197	6kg 75	77	
	20kg 127	25	55	20kg 10	4	37	8kg 47	49	
	30kg 90	14	31	30kg 0	0	0	5kg 113	114	
	40kg 69	8	18	40kg 0	0	0	10kg 37	38	
Lead 5	20kg 256	29	76	20kg 24	9	152	15kg 12	12	
	30kg 188	16	43	30kg 0	0	0	16kg 9	9	
	40kg 96	10	28	40kg 0	0	0			
	50kg 33	6	18	50kg 0	0	0			

Note. Distance from center of slider top to center of gravity of object being carried at a guide service life of 10,000 km.

Static loading moment




(Unit: N·m)		
MY	MP	MR
70	95	110

Controller

Controller	Operation method
SR1-X05 RCX320 RCX221/222 RCX340	Programming / I/O point trace / Remote command / Operation using RS-232C communication
TS-X105	I/O point trace / Remote command
TS-X205	Remote command
RDV-X205-RBR1	Pulse train control

C8L



Effective stroke	150	200	250	300	350	400	450	500	550	600	650	700	750	800	850	900	950	1000	1050	
L	475	525	575	625	675	725	775	825	875	925	975	1025	1075	1125	1175	1225	1275	1325	1375	
A	0	1	1	2	2	3	3	4	4	5	5	6	6	7	7	8	8	9	9	
B	150	100	150	100	150	100	150	100	150	100	150	100	150	100	150	100	150	100	150	
C	8	10	10	12	12	14	14	16	16	18	18	20	20	22	22	24	24	26	26	
D	280	330	380	430	480	530	580	630	680	730	780	830	880	930	980	1030	1080	1130	1180	
Weight (kg) ^{Note 3}	3.9	4.2	4.5	4.8	5.1	5.4	5.7	6.0	6.4	6.7	7.0	7.3	7.6	7.9	8.2	8.5	8.8	9.2	9.5	
Maximum speed ^{Note 4} (mm/sec)	Lead 20	1000																		
	Speed setting	-																		
	Lead 10	600																		
	Lead 5	300																		
Speed setting	85%	75%	65%	60%	55%	50%	45%	40%	35%	30%	25%	20%	15%	10%	5%	5%	5%	5%	5%	

Note 1. Stop positions are determined by the mechanical stoppers at both ends.
 Note 2. Minimum bend radius of motor cable is R50.
 Note 3. Weight of models with no brake. The weight of brake-attached models is 0.3 kg heavier than the models with no brake shown in the table.
 Note 4. When the stroke is longer than 700mm, resonance of the ball screw may occur depending on the operation conditions (critical speed). In this case, reduce the speed setting on the program by referring to the maximum speeds shown in the table at the left.