

Programming box

PBX/PBX-E

▼Applicable controllers



RCX340

P.542


This programming box is applicable to three languages, “Japanese”, “English”, and “Chinese”. Use of a color display makes it possible to improve the visibility. Work to add or edit functions becomes easy, allowing even personnel without programming skill to operate this programming box.

A function to save the controller data into the USB memory is incorporated.


■ PBX/PBX-E basic specifications

Name	PBX	PBX-E
External view		
Applicable controllers	RCX340	
Model	Japanese language model	KCX-M5110-1J (5m) KCX-M5110-3J (12m)
	English language model	KCX-M5110-1E (5m) KCX-M5110-3E (12m)
	Chinese language model	KCX-M5110-1C (5m) KCX-M5110-3C (12m)
Display screen	Color LCD (320 × 240 dot)	
Emergency stop button	Normally-closed contact (with lock function)	
Enable switch	Not provided	3-position type
Manual lock selector switch	90°, 2-notch	
Power	+12 V DC	
Operating environment	Ambient temperature for use: 0 to 40 °C, Ambient temperature for storage: -10 to 60 °C Humidity: 35 to 80% (no condensation)	
Dimensions (mm)	W141 × H245 × D45 (excluding projecting parts)	
Cable length	5 m or 12 m (Select either)	
Weight	440 g (excluding the cable)	460 g (excluding the cable)

■ Part names and function



■ PBX-E rear side



■ Display language switching USB for PBX

	Model
Display language switching USB for PBX	KCX-M6498-00
USB cable	KCX-M657E-00