

TS-X / TS-P specification selection table

Some specifications are automatically determined by the robot model.

TS-X

			T4LH / C4LH	T5LH / C5LH	T6L / C6L	T9	T9H	F8 / C8	F8L / C8L	F8LH / C8LH	F10 / C10	F14 / C14	F14H / C14H	F17 / C17	F17L / C17L	F20 / C20	F20N	N15 / N15D	N18 / N18D	B10	B14	B14H	R5	R10	R20	
Power supply voltage / Current sensor	TS-X	105	●	●	●	●		●	●	●	●	●								●	●	●	●	●		
		110					●						●													●
		205	●	●	●	●		●	●	●	●	●	●								●	●	●	●	●	
		210					●						●													●
		220													●	●	●	●	●	●						
Regenerative unit	No entry (None)					(1)	(2)				(1)	(1)	(2)	(3)		(3)	(4)						(5)			
	R (RGT)					(1)	(2)				(1)	(1)	(2)	(3)	●	(3)	(4)	●	●				(5)			

(1) Regenerative unit is needed if using in a perpendicular position and movement stroke is 700mm or more.

(2) Regenerative unit is needed if using in a perpendicular position.

(3) Regenerative unit is needed if using in a perpendicular position, using at maximum speeds exceeding 1000mm per second, or if using high leads (40).

(4) Regenerative unit is needed if using at maximum speeds exceeding 1000mm per second.

(5) Regenerative unit is needed if using at maximum speeds exceeding 1250mm per second.

TS-P

			MR12/12D	MF7/7D	MF15/15D	MF20/20D	MF30/30D	MF75/75D
Power supply voltage / Current sensor	TS-P	105	●					
		110		●	●	●		
		205	●					
		210		●	●	●		
		220					●	●
Regenerative unit	No entry (None)		●	●	●			
	R (RGT)					●	●	
	R (RGU-2)							●