

# SRD04

Rod type (With support guide)

● CE compliance

● Origin on the non-motor side is selectable: Lead 6, 12



## Ordering method

### SRD04

Model	Lead	Model	Brake	Origin position	Bracket plate	Stroke	Cable length
	12: 12mm 06: 6mm 02: 2mm	S: Straight model U: Space-saving model (motor installed on top)	N: With no brake B: With brake	N: Standard Z: Non-motor side	N: No plate H: With plate	50 to 300 (50mm pitch)	1K: 1m 3K: 3m 5K: 5m 10K: 10m

S2	I/O
Robot positioner S2: TS-S2	NP: NPN PN: PNP CC: CC-Link DN: DeviceNet™ EP: EtherNet/IP™ PT: PROFINET GW: No I/O board

SH	I/O	Battery
Robot positioner SH: TS-SH	NP: NPN PN: PNP CC: CC-Link DN: DeviceNet™ EP: EtherNet/IP™ PT: PROFINET GW: No I/O board	B: With battery (Absolute) N: None (Incremental)

SD	1
Robot driver SD: TS-SD	I/O cable 1: 1m

Note 1. See P.337 for grease gun nozzles.  
Note 2. When "2mm lead" is selected, the origin position cannot be changed (to non-motor side).  
Note 3. If changing from the origin position at the time of purchase, the machine reference amount must be reset. For details, refer to the manual.



Note 4. The robot cable is flexible and resists bending.  
Note 5. See P.600 for DIN rail mounting bracket.  
Note 6. Select this selection when using the gateway function.

## Basic specifications

Motor	42 □ Step motor
Resolution (Pulse/rotation)	20480
Repeatability (mm)	+/-0.02
Deceleration mechanism	Ball screw φ8 / Ball screw φ10
Ball screw lead (mm)	12 / 6 / 2
Maximum speed (mm/sec)	500 / 250 / 80
Maximum payload (kg)	Horizontal: 25 / 40 / 45 Vertical: 4 / 11 / 24
Max. pressing force (N)	150 / 300 / 600
Stroke (mm)	50 to 300 (50pitch)
Lost motion	0.1mm or less
Rotating backlash (°)	+/-0.05
Overall length (mm)	Horizontal: Stroke+263 Vertical: Stroke+303
Maximum outside dimension of body cross-section (mm)	W48 × H58
Cable length (m)	Standard: 1 / Option: 3, 5, 10


Note 1. The maximum speed needs to be changed in accordance with the payload.  
See the "Speed vs. payload" graph shown on the right. For details, see P. 336.  
Additionally, when the stroke is long, the maximum speed is decreased due to the critical speed of the ball screw.  
See the maximum speed table shown at the lower portion of the drawing.

## Speed vs. payload



## Running life

5000 km on models other than shown below.  
Running life of only the model shown below becomes shorter than 5000 km depending on the payload, so check the running life curve.



Note. See P.337 for running life distance to life time conversion example.

## Controller

Controller	Operation method	Controller	Operation method
TS-S2	I/O point trace / Remote command	TS-SD	Pulse train control

## SRD04 Straight model S

