









DT125R TECHNICAL SPECIFICATIONS

ENGINE	
Туре	2-stroke, liquid-cooled crankcase
	reed-valve, single cylinder
Displacement	124cc
Bore and stroke	56 x 50.7 mm
Compression ratio	6.7 : 1
Maximum power	14 HP (10.4 kW) @ 7,000 rpm
Maximum torque	1.45 kg-m (14.2 Nm) @ 7,000 rpm
Lubrication	Autolube
Carburation	MIKUNI TM28SS/1
Ignition	C.D.I.
Starter system	Kick
Fuel tank capacity	10 litres
Oil tank capacity	1.2 litres
Transmission	6-speed, constant mesh
Final transmission	Chain
CHASSIS	
Overall length	2,170 mm
Overall width	830 mm
Overall height	1,255 mm
Seat height	885 mm
Wheelbase	1,415 mm
Min. ground clearance	315 mm
Dry weight	116 kg
Front suspension	Telescopic fork
Rear suspension	Swinging arm (Monocross)
Front brake	Single disc 230 mm Ø
Rear brake	Single disc 220 mm Ø
Front tyre	2.75-21 45P
Rear tyre	4.10-18 59P

Always wear a helmet, eye protection and protective clothing. Yamaha encourage you to ride safely and respect fellow riders and the environment. Specifications and appearance of Yamaha products shown here may vary according to requirements and conditions, and are subject to change without notice. For further details, please consult your Yamaha dealer.

