



YAMAHA MOTOR POWERED PRODUCTS CO.,LTD.

200-1 Sakagawa, Kakegawa,
Shizuoka 436-0084, Japan

New Experience of work

UMX



202005



EXPAND YOUR WORKING FIELD











Specifications

Dimensions	UMX
Overall length	3,032 mm
Overall width	1,253 mm
Overall height (sun top)	1,824 mm
Wheel base	1,961 mm
Minimum ground clearance	115 mm
Tyre size	20 x 10 - 10 (4 Ply Rated)
Cargo box material	Aluminium
Cargo bed capacity	363 kg
Cargo bed size (LxWxH)	1,044 mm x 1,167 mm x 302 mm
Frame	Robotic welded automotive ladder-style steel frame protected with a multi-step full-immersion phosphate treatment, electro-deposition epoxy-based coating, and an electrostatic applied polyester.
Body	Thermoplastic olefin, 2-part top coat of automotive-grade polyurethane
Front suspension	Fully independent automotive-style strut suspension
Rear suspension	Swing arm with coil springs
Brakes	Self-adjusting, mechanical drum brakes on all 4 wheels
Performance	UMX AC
Curb weight (with Suntop, Battery, Oil, and Fuel)	640 kg
Output rating	6.7 HP (5.0 kW)
Maximum forward speed *Adjustable	31 km/h
Turning radius	3.98 metre
Performance	UMX EFI
Curb weight (with Suntop, Battery, Oil, and Fuel)	469 kg
Engine type	Low emission single cylinder 60° incline OHV
Output rating Carburetor / Fuel supply	10.63 kW (14.3 HP) at 3,600 rpm Electronic Fuel Injection
Fuel tank capacity	20 litres
Maximum forward speed	31 km/h
Turning radius	3.98 metre